

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

Astro-Vest (TM) investment [NA]

Revision 4
Revision date 2017-03-24

1.1. Product identifier

Product name Astro-Vest (TM) investment [NA]

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard,

Maumee, OH 43537 USA

Web www.ransom-randolph.com

Telephone +1 (419) 865-9497 **Fax** +1 (419) 865-9997

Email RR.SDS@dentsply.com

Email address of the RR.SDS@dentsply.com

competent person

Sompotont person

1.4. Emergency telephone number

Emergency telephone number

Company

USA +1 419 865 9497

Ransom & Randolph Co.

07:30 to 16:30 (Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient compostion maybe withheld, to protect trade secrets.

Hazard pictograms



Signal Word

Hazard Statement

Danger

Carc. 1A: H350 - May cause cancer inhalation.

STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

Revision Revision date 2017-03-24

2.2. Label elements

	inhalation.
Precautionary Statement:	P201 - Obtain special instructions before use.
Prevention	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 - Wash (hands) thoroughly after handling.
	P270 - Do no eat, drink or smoke when using this product.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P285 - In case of inadequate ventilation wear respiratory protection.
Precautionary Statement:	P308+P313 - IF exposed or concerned: Get medical advice/attention.
Response	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement:	P405 - Store locked up.
Storage	
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations
Disposal	
2.3. Other hazards	
Other hazards	Product contains crystalline silica.

Other hazards	Product contains crystalline silica.

Further information

Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
phosphate binder (proprietary)					1 - 10%	Xi; R36/38	
phoshate binder 2 (proprietary)					1 - 10%	Xi; R36/38	
Magnesium Oxide		01309-48-4	215-171-9		1 - 10%	Xn; R20 Xi; R37/38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
quartz (conc. >/= 1.0%)		14808-60-7	238-878-4		60 - 70%	Carc. 1A: H350; STOT RE 1: H372;	
phosphate binder (proprietary)					1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
phoshate binder 2 (proprietary)					1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
silica (cristobalite conc. >/= 1.0 %)		14464-46-1	238-455-4		20 - 30%	Carc. 1A: H350; STOT RE 1: H372;	

Further information

Full text for all Risk Phrases r	mantionad in this s	ection are displ	aved in Section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

Revision 4
Revision date 2017-03-24

	Revision date 2017-03-24
4.2. Most important symptoms a	nd effects, both acute and delayed
Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.
4.3. Indication of any immediate	medical attention and special treatment needed
Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	·
	No environmental requirements.
6.3. Methods and material for co	ontainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	' ·
	See section [2, 8 & 13] for further information.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handling	g
	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after
700 80 5 5 6	handling the product.
7.2. Conditions for safe storage,	
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contro	ols/personal protection

8.1. Control parameters

Revision 4
Revision date 2017-03-24

8.1. Control parameters	
	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / [2(% Silica + 2)] TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, quartz - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / (% Silica + 2) TWA PEL (respirable fraction).
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.
Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Off white
Odour	Slight
Odour threshold	Not applicable.
pH	6 - 8
Melting point	No data available
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2.6 (H2O = 1 @ 20 °C)
Fat Solubility	Not applicable.
Partition coefficient	No data available
Autoignition temperature	Not applicable.
Viscosity	Not applicable.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Revision Revision date 2017-03-24

9.2. Other information

Conductivity Surface tension

No data available

Not applicable.

Gas group

Not applicable.

Benzene Content Lead content Not applicable.

VOC (Volatile organic

Not applicable.

compounds)

Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

No Significant Hazard.

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

Serious eye damage/irritation

No irritation expected.

Respiratory or skin sensitisation

No sensitizaton effects reported.

Germ cell mutagenicity

No mutagenic effects reported.

Carcinogenicity

Known Human Carcinogens (Category 1).

Reproductive toxicity STOT-single exposure No observed effect level. No observed effect concentration.

STOT-repeated exposure

No known adverse health effects.

Chronic effects

Prolonged inhalation of respirable crystalline silica

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with

Revision 4 Revision date 2017-03-24

11.1. Information on toxicologic	cal effects
	silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."
	(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
SECTION 12: Ecological in	formation
12.2. Persistence and degrada	bility
	No data is available on this product.
12.3. Bioaccumulative potentia	I
	Does not bioaccumulate.
Partition coefficient	
	Astro-Vest (TM) investment No data available [NA]
12.4. Mobility in soil	
	Not determined.
12.5. Results of PBT and vPvB	3 assessment
	Not determined.
12.6. Other adverse effects	
	Not applicable.
SECTION 13: Disposal cor	siderations
13.1. Waste treatment method	s
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport inf	ormation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
1 1 1 1 1 1 1	The product is not classified as dangerous for carriage.
	- The production of the same and the same an

Revision 4
Revision date 2017-03-24

	Tevision date 2017-00-24
14.3. Transport hazard class(es	
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for us	er
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

_					
Re	aı	ıla	Hi.	^r	10
170	чυ	Пa	ш	v	13

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: Astro-Vest ™ is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Chronic health

Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite (< 95 %);

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information



Revision 4 Revision date 2017-03-24

Other information				
Revision	This document differs from the previous version in the following areas:.			
	2 - 2.1.2. Classification - EC 1272/2008.			
	2 - Hazard pictograms.			
	2 - Signal Word.			
	2 - Precautionary Statement: Prevention.			
	2 - Precautionary Statement: Response.			
	2 - Precautionary Statement: Storage.			
	2 - Precautionary Statement: Disposal.			
Text of risk phrases in Section	R20 - Harmful by inhalation.			
3	R36/38 - Irritating to eyes and skin.			
	R37/38 - Irritating to respiratory system and skin.			
Text of Hazard Statements in	Carc. 1A: H350 - May cause cancer .			
Section 3	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .			
	Skin Irrit. 2: H315 - Causes skin irritation.			
	Eye Irrit. 2: H319 - Causes serious eye irritation.			
Further information				
	Training			
	Workers must be informed of the presence of crystalline silica and trained in the proper use and			
	handling of this product as required under applicable regulations.			
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,			
	storage and handling of the product. This information is correct to the best of our knowledge and			
	belief at the date of publication however no guarantee is made to its accuracy. This information			
	relates only to the specific material designated and may not be valid for such material used in			
	combination with any other materials or in any other process.			